

---

WAVECOM Decoder

# W61PC/LAN Specifications

## V7.3

By WAVECOM ELEKTRONIK AG



**WAVECOM**<sup>®</sup>  
NACHRICHTENTECHNIK

PUBLISHED BY  
WAVECOM ELEKTRONIK AG  
Hammerstrasse 8  
CH-8180 Buelach  
Switzerland

Phone           +41-44-872 70 60  
Fax             +41-44-872 70 66  
Email:         info@wavecom.ch  
Internet:       <http://www.wavecom.ch>

© by WAVECOM ELEKTRONIK AG. All rights reserved.

Reproduction in whole or in part in any form is prohibited without written consent of the copyright owner.

The publication of information in this document does not imply freedom from patent or other protective rights of WAVECOM ELEKTRONIK AG or others.

All brand names in this document are trademarks or registered trademarks of their owners.

Specifications are subject to change without further notice.

Printed: Thursday, November 24, 2011

---

# Contents

<b>Protocols</b>	<b>2</b>
List of Abbreviations, Remarks .....	2
HF-Protocols .....	2
VHF/UHF-Protocols .....	5
SAT-Protocols.....	7
FAX and Modem Protocols.....	7
W-Sat-email-Decoder.....	8
<b>List of Alphabet</b>	<b>9</b>
<b>Demodulator</b>	<b>10</b>
<b>Analysis Function</b>	<b>11</b>
<b>General Software Characteristics</b>	<b>12</b>
<b>Options</b>	<b>13</b>
CLASSIFIER-NB .....	13
HF .....	13
Classifier Code Check (CCC) with Look-Up Table.....	14
<b>W61PC &amp; W61LAN Hardware</b>	<b>15</b>
<b>Ordering Information</b>	<b>17</b>
<b>Index</b>	<b>19</b>





# Protocols

---

## List of Abbreviations, Remarks

\* Currently being developed

 New in list

Parameters depend on the selected protocol. The full parameter ranges can only be used, when working with the source code.

Specifications may be changed without prior notice.

---

## HF-Protocols

HF-Protocols
ALE-400
ALF-RDS
ALIS
ALIS-2
ARQ6-90
ARQ6-98
ARQ-E
ARQ-E3
ARQ-M2-242
ARQ-M2-342
ARQ-M4-242
ARQ-M4-342
ARQ-N
ASCII
AUM-13
AUTOSPEC
BAUDOT
BR-6028 (BAUDOT and ASCII)
BULG-ASCII
CHU
CIS-11
CIS-12 (HEX output)
CIS-14
CIS-36

HF-Protocols
CIS-36-50
CIS-50-50
CLOVER-2 ( ARQ, all CRC's)
CLOVER-2000 (ARQ, all CRC's)
CODAN (SELCAL)
CODAN-9001
COQUELET-13
COQUELET-8
COQUELET-80
CV-786
CW-MORSE
DCS SELCAL
DGPS
DUP-ARQ
DUP-ARQ-2
DUP-FEC-2
EFR
FEC-A
FELDHELL
FM-HELL
GMDSS/DSC-HF
G-TOR
GW-FSK
GW-OFDM
GW-PSK
HC-ARQ
HF-ACARS (HF DL)
HNG-FEC
ICAO-SELCAL (ANNEX 10)
LINK-11
MD-674
MFSK-16
MFSK-20
MFSK-8
MIL-188-110-16TONE (-110A/B App. A)
MIL-188-110-39TONE (-110A/B App. B)

HF-Protocols
MIL-188-110A, Serial Tones, 75-4800 bps
MIL-188-110B (App. C), STANAG 4539
MIL-188-110B, 3200-12800 bps
MIL-188-141A (ALE)
MIL-188-141B (BW0, BW1, BW4 data)
MIL-188-141B (BW2 & BW3 id only)
MIL-M-55529 NB/WB
OLIVIA
PACKET-300/600
PACTOR (all CRC's)
PACTOR-FEC (all CRC's)
PACTOR-II (all CRC's)
PACTOR-II-FEC (all CRC's)
PACTOR-III (all CRC's)
PICCOLO-MK12
PICCOLO-MK6
POL-ARQ
PRESS-FAX
PSK-10
PSK-125 (BPSK, QPSK) and FLARC extension
PSK-125F
PSK-220F
PSK-250 (BPSK, QPSK) and FLARC extension
PSK-31 (BPSK, QPSK)
PSK-31-FEC
PSK-63 (BPSK, QPSK) and FLARC extension
PSK-63F
PSK-AM
ROBUST-PACKET
RUM-FEC
SI-ARQ
SI-AUTO
SI-FEC
SITOR-ARQ
SITOR-AUTO
SITOR-FEC



## HF-Protocols

SP-14

SPREAD-11

SPREAD-21

SPREAD-51

SSTV Automatic

SSTV Martin 1, 2, 3 & 4

SSTV Robot 8s, 12s, 24s & 36s

SSTV SC-1 16 & 32s

SSTV SC-1 8s, 16s & 32s

SSTV Scottie 1, 2, 3 & 4

SSTV Wraase SC-1 24s, 48s & 96s

SSTV Wraase SC-2 20s, 60s, 120s & 180s

STANAG 4285 75-3600 bps

STANAG 4415 75 bps (NATO ROBUST)

STANAG 4481-FSK (KG-84)

STANAG 4481-PSK

STANAG 4529 75-1800 bps

STANAG 4539 3200-12800 bps

STANAG 5065-FSK

SWED-ARQ

TWINPLEX ARQ

VISEL

WEATHER-FAX

## VHF/UHF-Protocols

### VHF/UHF-Protocols

ACARS

AIS

APCO-25

ASCII

ATIS (Selcal Digital)

BIIS

CCITT (Selcal Analog)

CTCSS (Selcal Analog)

DCS SELCAL

DGPS

VHF/UHF-Protocols
DMR with Live Voice (Digital Mobile Radio, XiR, or MOTOTRBO)
dPMR with Live Voice
DTMF (Selcal Analog)
DZVEI (Selcal Analog)
EEA (Selcal Analog)
EIA (Selcal Analog)
ERMES
EURO (Selcal Analog)
FLEX
FMS-BOS (Selcal Digital)
GMDSS/DSC-VHF/UHF
GOLAY
MOBITEX-1200 (with partial OVLS extension)
MOBITEX-8000
MODAT (Selcal Analog)
MPT-1327
NATEL (Selcal Analog)
NMT-450
NWR-SAME
PACKET-1200
PACKET-9600
PCCIR (Selcal Analog)
PDZVEI (Selcal Analog)
POCSAG
PZVEI (Selcal Analog)
SKYPER (POCSAG)
TETRA with Live Voice
VDEW (Selcal Analog)
VDL-M2
X.25
ZVEI-1 (Selcal Analog)
ZVEI-2 (Selcal Analog)
ZVEI-3 (Selcal Analog)
ZVEI-VDEW (Selcal Digital)

---

# SAT-Protocols

Single channel INMARSAT C/B/M/mM Monitoring System, with FAX/Voice/Data File-Recording, FAX-Viewer for B/M/mM, B Voice-Playback. Live Voice, Sat-Email-Decoder (Option).

SAT Protocols
AMSAT-P3-D
INMARSAT-AERO-P
INMARSAT-B-C-TFC (return)
INMARSAT-B-Data (forward)
INMARSAT-B-FAX (forward)
INMARSAT-B-HSD (forward, High Speed Data)
INMARSAT-B-TEL (forward), Live Voice
INMARSAT-B-TELEX-MM (forward)
INMARSAT-B-TELEX-SM (forward)
INMARSAT-C-EGC (Enhanced Group Calls)
INMARSAT-C-TDM
INMARSAT-C-TDMA
INMARSAT-C-TDM-EGC
INMARSAT-M -DATA (forward)
INMARSAT-M -FAX (forward)
INMARSAT-M -TEL (forward), Live Voice
INMARSAT-mM-DATA (forward)
INMARSAT-mM-FAX (forward)
INMARSAT-mM-TEL (forward) ask
NOAA-GEOSAT
ORBCOMM

---

# FAX and Modem Protocols

FAX and Modem Protocols W-61PC
FAX-G3 T4 / T6 / JPEG / JBIG T.30 protocol with ECMM
FAX-G3-V.17
FAX-G3-V.27ter
FAX-G3-V.29
FAX-G3-V.34hdx
BELL103

### FAX and Modem Protocols W-61PC

BELL212A

V.21

V.22 / V22bis

V.23

---

## W-Sat-email-Decoder

This is a separate product and is not part of W-CODE or W61PC.

### List of Decoded INMARSAT Email Protocols

AMOS (Mails and attachments)

Dualog

GlobeWireless (Mails and attachments)

GTMail

MS-RAS PPP

Rydex (Mails and attachments, attachment are not always renamed)

se@comm

Skyfile (Mails and attachments)

Stratos

# List of Alphabet

List of Alphabets
Chinese (7Bit ASCII)
HEX
ITA-1 Latin
ITA-2 Baghdad70 Arabic
ITA-2 Baghdad80 Arabic
ITA-2 Cyrillic
ITA-2 Danish-Norwegian
ITA-2 Hebrew
ITA-2 Latin
ITA-2 Latin Transparent
ITA-2 Swedish
ITA-2 TASS Cyrillic
ITA-2 Third Shift Cyrillic
ITA-2 Third Shift Greek
ITA-5 Bulgarian
ITA-5 Danish-Norwegian
ITA-5 French
ITA-5 German
ITA-5 Swedish
ITA-5 US
Morse Arabic
Morse Cyrillic
Morse Greek
Morse Hebrew
Morse Latin
Morse Scandinavian
Morse Spanish
User defined 5-bit Alphabets based on UNICODE

# Demodulator

Demodulators (Biterror rate within 3 dB of theory (white Gaussian noise, non fading channel))
AM for METEOSAT and NOAA-GEOASAT FAX transmissions
BPSK, 10-12000 symbols/s
CTCSS
CW Morse, 10-500 WPM, Center freq. 0.5 kHz-3.5 kHz, BW 100 Hz-1.2 kHz, AFC On/Off
DPSK, DBPSK, DQPSK, D8PSK, D16PSK, 10-12000 symbols/s
DTMF
DXPSK, dual carrier adaptive modulation, 2DPSK-D16PSK, 100 Baud
FAX-G3-V.17, FAX-G3-V.27ter, FAX-G3-V.29, FAX-G3-V.34hdx, BELL103, BELL212A, V.21, V.22 / V22bis, V.23
FFSK, 10-12000 Baud, Shift 50 Hz-16 kHz
FSK, 10-2400 Baud, Shift 50 Hz-3.5 kHz, Center freq. 0.5 kHz-3.5 kHz
GFSK, 10-12000 Baud, Shift 50 Hz-16 kHz
Mark-Space FSK, 10-300 Baud, Shift 50 Hz-3.5 kHz, Center freq. 0.5 kHz-3.5 kHz
MFSK, Tone length 4-1000 ms / max. 64 Tones, Shift 50 Hz-3.5 kHz
OQPSK, 10-12000 symbols/s
QPSK, 10-12000 symbols/s
Software AM/ FM Demodulator for IF Inputs

# Analysis Function

Analysis Functions
Autocorrelation up to 200'000 bits
Automatic analysis & decoding software for all data and FAX-G3 modulations
Automatic CRC recognition of all PACTOR-II and PACTRO-II-FEC systems
Automatic message type detection (ITA-2, ITA-5 and sync/async) for STANAG and MIL-Std
Bit correlation analysis. Raw FSK analysis: Graphical display of demodulated data on a raster time line. For visual recognition of character and block lengths
Bit length analysis. Graphical display of demodulated data, with automatic calculation of bit length with bit pattern display
Code check for FSK codes
FSK analysis
Manual measurement of the frequency shift(s) with movable cursors
MFSK analysis for HF: Graphical display of MFSK tones with histogram
Oscilloscope, real time, resolution up to 200 us/div
Phase plane display, HF, VHF/UHF Indirect BPSK, QPSK, OQPSK DPSK, 25-2400 Baud
Phase plane display, VHF/UHF Direct BPSK, DPSK, QPSK, OQPSK, 100-12000 Baud
Real-time FFT, averaging: 1-64 values, bandwidth 0.5, 1, 2, 4, 24, 48 kHz & 96 kHz and adjustable cursors, 20 frames/sec
Sonagram and FFT tuning display
Sonagram, real time display with cursor functions and history (full scrolling)
Symbol rate HF, VHF/UHF Indirect, Analysis 30-4000 Baud
Symbol rate VHF/UHF Direct, Analysis 30-24000 Baud
VHF/UHF Selcal analysis: Graphical display of FSK data for Selcal signal analysis
Waterfall, real time display with cursor functions

# General Software Characteristics

General Software Characteristics
ALARM MONITOR, automatic detected text-string saving to HD or LAN, SMS output
Automatic insertion of time stamps
Bitstream: raw, synchronized FSK bitstream available through remote control interface
Bitstream: raw, synchronized none adaptive PSK bitstream available through remote control interface
File formats: TXT, BMP, Unicode, WAVECOM (with timestamps)
FSK baudrate history display with full graphical recall / averaging and cursor functions
FSK shift history display with graphical recall/averaging, cursor functions
Message type for most MIL-STD and STANAG codes (sync/async, data bits, parity bits, stop bits, MSB/LSB, ITA2/ITA5(ASCII)/HEX/STANAG5066
Pass-band filters in most codes
Pass-band tuning in FFT display in most codes
SERIAL LINK, serial data output over COM1-16
Sound card input, 16bit, 48 kHz, Stereo
STANAG5066 parser in MIL-STD and STANAG codes
TCP/IP direct data (IQ and PCM) interface for streaming and digital receivers (PXGF, IP-CONF)
TCP/IP Remote Control with WAVECOM GUI, full functionality over LAN/Internet (encrypted and speed optimized)
Unlimited scroll back buffers for text and graphic
Up to 8 decoders/computer
USB-License-Dongle
Virtual Audio Cable (VAC) support
WAV files playback and decoding, loop mode
XML Remote Control (API for C++ and C#, XML over TCP/IP)



# Options

## CLASSIFIER-NB

### HF

HF Classifier	
Bandwidth HF	4 kHz or 8 kHz
Sampling interval (Ts)	1.6 or 3.2 sec
CW	Ts=1.6: 6 to 60 Bd Ts=3.2: 3 to 60 Bd
FSK	30 to 3000 Bd Shift ≤ 3500 Hz Modulation index: 0.5-20 Continuous available during sampling interval
FSK-4/F7B	30 to 300 Bd, Shift ≤ 3500 Hz
MFSK	4-36 Tones
PSK 2/4 Variant A/B	30 to 3000 Bd
PSK 8/16 Variant A/B	30 to 3000 Bd
CIS-12	120 Bd
OFDM	25-512 Carriers Tg/Tu = 1/1 to .1/8 ≥25 Bd
OQPSK	25 Bd to 30 kBd
Operating	Display of classified signals in FFT Continuous mode Classifier Code Check with look-up table

Quality of modulation classification		
CW		18 dB ( $E_b/N_0$ )
FSK	m=0.8; 100-2400 Bd	12 db ( $E_b/N_0$ )
	m=0.8; 50 Bd	15 db ( $E_b/N_0$ )
	m≥2; 100-2400 Bd	14 db ( $E_b/N_0$ )
	m≥2; 50 Bd	16 db ( $E_b/N_0$ )
PSK 2/4 Variant A/B	100-2400 Bd	14 dB ( $E_b/N_0$ )
PSK 8/16 Variant A/B	100-2400 Bd	16 dB ( $E_b/N_0$ )

Accuracy of measured parameters		
CW	baud rate	5 %
FSK	baud rate	0.3 %
	center frequency	2% of baud rate
PSK	baud rate	0.2 %
	center frequency	0.15 % of baud rate

## Classifier Code Check (CCC) with Look-Up Table

Classifier Code Check Characteristic		
Look up table implemented as XML file		
XML Editor for table maintenance		
Data entry templates for FSK, MFSK, (M)PSK, OFDM, CW		
Process Steps	P1	Only classification is performed, but no decoding.
	P2	Classification and table check are performed, but no decoding.
	P3	Classification, table check and code check are performed, but no decoding.
	P4	Classification and table check are performed and finally the signal is decoded if a mode with an associated, valid detector was found.
	P5	Classification, table check and code check are performed and finally the signal is decoded if a mode with an associated, valid detector was found.

# W61PC & W61LAN Hardware

Card Inputs	AFIF#1-3	IF70	EXT-DEM
Connector	SMA female	SMA female	Mini-DIN
Frequency range	50 Hz to 25 MHz	52.5 MHz to 87.5 MHz (SAW Filter)	Max. 12 kBit/s
Bandwidth	5 kHz to 500 kHz	5 kHz to 500 kHz	
Frequency raster DDS	1.0 Hz	1.0 Hz	
Signal level	2 mVrms to 0.5 Vrms 20 mVrms to 2.5 Vrms (with 20 dB attenuator)	20 mVrms to 2.5 Vrms	TTL up to RS-232C [0 V, +5 V] to [-12 V, +12 V]
Input impedance	> 1 kOhm	50 Ohm	>100 kOhm
Pin-out			2, 7 GND 5 EXT-MOD
Remarks			V1 Data Internal Synchronization

Hardware	W61PC	W61LAN-MK3
Concept	Half length board	Small Computer System
Dimensions (LxWxH mm)	168x106x22	268x195x100
Weight in kg	0.2	5 kg
PCI bus, 32 bit	rev. 2.2 or above	-
Power requirement, (typ, values)	1.0A@+3.3V 0.4A@+12V	9-30V (max. 120 W)
AC Power supply	-	100-240V AC 2A 50/60 Hz
Operating temperature range	0° C to 50°C	0° C to 40°C, free airflow
Case temperature range		0° C to 55°C
Storing temperature range	0° C to 70°C	0° C to 70°C
Relative humidity (non-condensing)	< 95 %	10-90 %
Sound card input: maximum sampling rate	48 kHz	48 kHz
External Demodulator Input	✓	✓
Wideband AF/IF Input, 50 Hz-25 MHz, tunable, requires filtered AF/IF signal output, Input impedance >1 kOhm	3	3
70 MHz, Wideband IF Input, 52.5 MHz-87.5 MHz,	1	1

Hardware	W61PC	W61LAN-MK3
tunable, Input impedance >50 Ohm		
AF / IF / HF Connectors	SMA	SMA
A/D Converter	14 bit	14 bit
Dynamic range	> 60 dB	> 60 dB
Direct digital synthesis DDS	FPGA	FPGA
DDS frequency resolution	< 1 Hz	< 1 Hz
DDC, (digital down conversion) with 96 db dynamic range	+	+
MTBF	>20'000	NA
Conformity	EN 55022:2004 class B, EN55024:2003, EN6100-6-2:2005, EN 6100-4-3:1000-2700 MHz, EN 50371:2002	CE, FCC
OS	Tested with Windows XP, Windows 7, Server 2008, 32/64 Bit, English	Win7 Pro 32-bit, English
CPU	min. P4, 1.6 GHz	Intel Core- Mob, i5-520M/2.4
Memory	min. 1 GB	DDR3-RAM 1 GB PC1333 CL9
Harddisk	min. 40 GB	160 GB, 5400, 8MB, 24h/7d
LAN	-	2 x 10MB/100MB/1GB
Serial ports	-	3 x RS232, 1 x RS232/422/485
USB	-	2 x USB 2.0 Front, 4 x USB 2.0 Back
eSATA	-	2
Audio	-	1x Mic-In, 1x Speaker-Out
Video	min. 1024x768	1 x VGA, 1 x DVI-I
Keyboard/Mouse	Computer	2 x PS/2 or USB
Sound card sampling rate precision (if AF/IF is not used)	<100 ppm, <20ppm recommended	<100 ppm, <20ppm recommended

# Ordering Information

Ordering Information	
Documentation	English user manual
Online Help	English
Software	Installation DVD with the latest software version and .wav signal samples
Updates	Software update by DVD
Warranty	One year on hardware



# Index

## A

Analysis Function 11

## C

Classifier Code Check (CCC) with Look-Up Table  
14

CLASSIFIER-NB 13

## D

Demodulator 10

## F

FAX and Modem Protocols 7

## G

General Software Characteristics 12

## H

HF 13

HF-Protocols 2

## L

List of Abbreviations, Remarks 2

List of Alphabet 9

## O

Options 13

Ordering Information 17

## P

Protocols 2

## S

SAT-Protocols 7

## V

VHF/UHF-Protocols 5

## W

W61PC & W61LAN Hardware 15

W-Sat-email-Decoder 8